# Control iD

## Multifunctional Access Controller iDAccess

iDAccess is an Access Controller with compact and modern design, that is capable of efficiently and speedily controlling people entering and leaving a facility. Each feature was designed with the most modern technologies to enable user-friendly operation. iDAccess is integrated with iDCloud making cloud management and contingency possible.

- Easy to install and operate
- Touchscreen display
- User-friendly menu
- Fingerprint, password and RFID reader (MiFare or 125kHz)
- Embedded web software (no installation required)
- Alarm monitoring and triggering



### Control iD

#### **iDAccess**

Multifunctional Access Controller

#### **TECHNICAL SPECIFICATIONS**

#### **ACCESS CONTROL**

#### Door Control

2 doors with individual inputs for REX button and door sensor

**User Capacity** More than 200.000 registered users

**Fingerprint Capacity** 

Up to 2.000 fingerprints in standalone

Customized by time, group and department

**Transaction Log Capacity** 

Over 200.000 records

**iDCloud** 

Cloud monitoring, synchronization and backup. Sold separately.

I/Os

2 separate output relays (220VAC/5A)

1 Wiegand Input (expandable up to 4) - also configurable as ABATRĂCK II

. 1 Wiegand Output (expandable up to 4) - also configurable as ABATRACK II

#### **ALARM CENTRAL**

**Alarm Inputs** 

Up to 5 individual zones with independent triggering times and polarities

**Alarm Output** 

Transistorized output up to 12VDC@10mA

**Tamper Detection** 

Configurable alarm for detecting when the terminal is removed

**Break-in Detection** 

Configurable alarm for detecting when a door is forced open

**Duress Alarm** 

Capable of enrolling a panic finger

#### COMMUNICATION

- . 1 Ethernet 10/100Mbps
- . 1 USB host 2.0
- 1 RS-485
- . GPRS and Wi-Fi optional

#### **MODES OF IDENTIFICATION**

Fingerprint
500 DPI Optical Fingerprint reader

**Proximity Reader** 

MiFare or RFID 125kHz (ASK / FSK / PSK)

**Password** 

Numeric password

#### **USER INTERFACE**

LCD TFT Colour Display with 2.6" (320x240) resistive touch screen

Internationalization

Multilanguage user interface

**Embedded Web Software** 

Complete access control software manageable from your



#### **GENERAL CHARACTERISTICS**

**Size and Dimensions** (length x height x width) 188mm x 70mm x 126mm - package dimensions

**Device Weight** 

212g Net Weight / 332g Gross Weight

**Power Supply** 12V (not included)

**Power Consumption** 2,4W (200mA) nominal

#### INTERCONNECTION DIAGRAM

